


Einschraubverschraubung,

L-Form 45°

CLMB



Verbindung zölliger Rohre mit NPT Innengewinden

Bestellnummer	Rohr AD D		T (NPT)	d min.	Schlüsselweite				A	B	ℓ	L	L ₁
	Zoll	mm			h		H						
					Zoll	mm	Zoll	mm					
CLMB 4 · 2N	1/4	6,35	1/8	4,82	1/2	12,70	9/16	14,28	15,24	17,78	17,27	24,63	16,51
CLMB 4 · 4N	1/4	6,35	1/4	4,82	1/2	12,70	9/16	14,28	15,24	17,78	17,27	24,63	21,08
CLMB 6 · 2N	3/8	9,52	1/8	4,82	5/8	15,87	11/16	17,46	16,76	19,30	20,57	27,94	18,28
CLMB 6 · 4N	3/8	9,52	1/4	7,11	5/8	15,87	11/16	17,46	16,76	19,30	20,57	27,94	22,86
CLMB 6 · 6N	3/8	9,52	3/8	7,11	13/16	20,63	11/16	17,46	16,76	19,30	21,84	29,21	24,13
CLMB 8 · 6N	1/2	12,70	3/8	9,50	13/16	20,63	7/8	22,22	22,86	21,84	21,84	32,00	24,13
CLMB 8 · 8N	1/2	12,70	1/2	10,41	13/16	20,63	7/8	22,22	22,86	21,84	21,84	32,00	28,95
CLMB 12 · 12N	3/4	19,05	3/4	15,11	1-1/8	28,57	1-1/8	28,57	24,38	21,84	23,87	34,03	30,98
CLMB 16 · 16N	1	25,40	1	22,00	1-3/8	34,92	1-1/2	38,10	31,24	26,41	28,19	40,38	37,84

Alle Maße in Millimetern, sofern nicht anders angegeben. Maße nur zur Information, Änderungen vorbehalten.